







INSTALLATION LIMITATIONS

The Weight Angel Safety System is designed with the following limitations

- Fall Arrest for one (1) users
- Fall Restraint for two (2) users
- Maximum roof pitch of five (5) degrees

Roofing Materials

- Sinale Ply Membrane
- Single Ply Bitumen Membrane with stone covering
- Single Ply Membrane Bitumen
- Concrete Deck

Weather


- Wet surfaces are tested
- Dry surfaces are tested

Conforms to EN795:2012

SafetyLiftinGear.com Unit R1D Rockingham Gate, Poplar Way West Cabot Park. Bristol. B511 0YW

- T | 0117 9381 600
- e | sales@safetyliftingear.com
- w | www.safetyliftingear.com

KEY SPECIFICATIONS



Made from Recycled Materials



Ø 1200mm

Weight 300 kg
Individual Weights 24 kg
Qty Weights 12 units
Weight of posts /supports 12 kg
Width 1200 mm
Height 465 mm

MATERIALS

POST	Polyuretnane
Eye Ring	SS 316
Cover	Aluminium
Bolts	SS 316

MATTING SPECIFICATIONS

Elastomer	Natural
Colour	Black
Quality	Commercial
Grade	N02
Hardness	70° shore a
S.G.	1.55g/cm³
Tensile MPA	4
Elongation	300%
Tear strength	12 kg/cm
Compression set	43%
Abrasion resistance	48/0 mm³
Operating temperature	-20° / +70° c

