

Hydraulic workshop crane model HWK KL S SILVERLINE

Capacity 500 and 1000 kg

For fitting and removing engines and for loading and unloading pallets.

Features

- With slewing hydraulic system and sensitive lowering valve, as standard.
- With folding device for space-saving storage of the crane.
- Chassis variants: V-shaped or parallel.
- With speed increasing ratio



Technical data model HWK KL S SILVERLINE

| Model | HWK KLS 0,5 | HWK KLS 0,5 | HWK KLS 1,0 | HWK KLS 1,0 |
|--|-------------|-------------|-------------|-------------|
| EAN-No. 4050939*** | ***018313 | ***018276 | ***018412 | ***018405 |
| Chassis form | parallel | V-shaped | parallel | V-shaped |
| Capacity with crane arm length A1, kg/mm | 500/1130 | 500/1130 | 1000/1130 | 1000/1130 |
| Capacity with crane arm length A2, kg/mm | 400/1230 | 400/1230 | 800/1230 | 800/1230 |
| Capacity with crane arm length A3, kg/mm | 350/1330 | 350/1330 | 700/1330 | 700/1330 |
| Capacity with crane arm length A4, kg/mm | 250/1430 | 250/1430 | 500/1430 | 500/1430 |
| Hook height at max. outermost position B, mm | 2200 | 2200 | 2200 | 2200 |
| Hook height at max. innermost position C, mm | 2080 | 2080 | 2080 | 2080 |
| Hook height at max. outermost position E, mm | 770 | 770 | 770 | 770 |
| Hook height at max. innermost position D, mm | 940 | 940 | 940 | 940 |
| Lifting height per pump stroke with/without load, mm | 20/80 | 20/80 | 20/80 | 20/80 |
| Operating pressure, bar | 150 | 150 | 290 | 290 |
| Hand effort at WLL, daN | 16 | 16 | 32 | 32 |
| Drive-through height G, mm | 1680 | 1680 | 1680 | 1680 |
| Underclearance height M, mm | 160 | 160 | 160 | 160 |
| Chassis length, total H, mm | 1820 | 1820 | 1820 | 1820 |
| Chassis width, inside/outside I/J, mm | 850/990 | 850/990 | 850/990 | 850/990 |
| Weight, kg | 138 | 132 | 156 | 150 |

