

## PHOENIX rescue harness QC, Red

H11QR

**Designed for fire and industrial rescue teams working in confined space, vertical rescue and fall arrest. Suitable for use with back-mounted breathing apparatus.**

### Features:

- Quick fit buckles for speed of fit
- Highly durable and comfortable to wear
- Integral back panel
- Semi-circular screwlink front attachment point
- High rear attachment point
- Protected leg loops
- Adjustable locking side buckles
- Captive buckles with large tabs

Integral back panel helps to maintain the structure of the harness.

Semi-circular screwlink permits safe multi-directional loading for casualty attachment.

Front attachment point is rated for fall arrest, it can be used for lowering or raising and suspension. Connector remains in position even if harness adjusted to fit.

Rear attachment point is rated for fall arrest and suspension, it is positioned high to be compatible with breathing apparatus and is reachable by the user.

Highly-durable Cordura sleeves provide added protection and wear resistance for the leg loops.

Adjustable side buckles allow for added comfort and sizing, but lock to prevent accidental release.

Buckles are captive to prevent disassembly and with large tabs for easy adjustment even wearing gloves.

### Options:

H11 - Standard leg loops



### Specifications:

*NB: specifications and colour may change without notice.*

Size: Universal  
EN Test Mass: 150kg  
Loading: Fall Arrest & Rescue loads

Conformity: EN361, EN1497

Materials: Polyamide, Stainless Steel and Plated screwlink.

Weight (kg): 1.25

Industries: Fire and rescue service. Can be used as part of both fall arrest and suspension systems.

### Attachment Points:

Dorsal  
Sternal

### Harness Measurements (cm):

Torso	95-130
Waist	-
Thigh	65-110