RIDGEGEAR PRODUCT DATA SHEET



RGL3

TWIN LEG WEBBING LANYARD & SHOCK ABSORBER RGL3

This twin leg lanyard is produced using our anti-bacterial protection webbing.

An industry standard, and usually the minimum equipment issued/ required with a harness for anyone working at height.

The extra leg allows progression between anchor points by means of double clipping, and also optimum safety by ensuring the user is always connected. The shock absorber pack will deploy in the event of a fall limiting the impact force on the user.

This system is generally used for tower climbing, steel erecting, scaffolding and maintenance to open structures.

EN 355:2002

Material:	26mm RIDGE Protect anti-bacterial polyester*
Fittings:	17mm steel screwgate karabiner (RGK1) Any other compatible EN 362 connectors
Max arrest force:	<6kN
Length(s):	1.4m (up to 140kg user) 1.8m (up to 100kg user) (including connectors)

Other lengths available upon request for a minimum order of 30 pieces. Lengths range from 1m to 1.4m for 140kg users and from 1.5m to 1.8m for 100kg users.

FEATURES



Shock absorber



* 14 times reduction in bacterial growth, according to ISO 20743:2013 contact with K.pneumoniae, commonly associated with healthcare infections such as E.coli

RIDGEGEAR LIMITED

Polson Street, Leek, Staffordshire, ST13 6BB

🤳 +44 (0)1538 384 108



< sales@ridgegear.com

🗧 ridgegear.com

bsi. ISO 9001 Quality Management Q05822

©2023 RIDGEGEAR Limited. All the information and imagery within this data sheet is subject to copyright. While we make every effort to ensure all the information here is correct and up-to-date, it is always worth checking with us before ordering. We reserve the right to change product specifications when necessary without prior notice.

