



## Carbine Hooks

### standard type

- **Material** : mild steel
- **Finish** : electro-galvanised
- **Note** : the minimum breaking load shown below is for guidance only  
the product is not suitable for lifting purposes

| diameter | length | width | width inside | width inside | minimum breaking load | weight per 100 pcs |
|----------|--------|-------|--------------|--------------|-----------------------|--------------------|
| a mm     | b mm   | c mm  | d mm         | e mm         | kg                    | kg                 |
| 4        | 40     | 14    | 5            | 7            | -                     | 0.6                |
| 5        | 50     | 16    | 7            | 8            | 100                   | 0.8                |
| 6        | 60     | 18    | 7            | 9            | 120                   | 1.6                |
| 7        | 70     | 22    | 9            | 10           | 180                   | 2.6                |
| 8        | 80     | 24    | 11           | 12           | 300                   | 4.4                |
| 9        | 90     | 26    | 11           | 12           | 330                   | 6.4                |
| 10       | 100    | 30    | 12           | 15           | 460                   | 9.3                |
| 11       | 120    | 36    | 14           | 18           | 600                   | 12.5               |
| 12       | 140    | 40    | 16           | 20           | 680                   | 19.5               |
| 13       | 160    | 44    | 20           | 22           | 800                   | 25.0               |
| 14       | 180    | 48    | 20           | 28           | 860                   | 35.0               |
| 15       | 200    | 52    | 22           | 29           | 920                   | 45.0               |



## Carbine Hooks

### with pressed thimble

- **Material** : mild steel
- **Finish** : electro-galvanised
- **Note** : the minimum breaking load shown below is for guidance only  
the product is not suitable for lifting purposes

| diameter | length | diameter inside thimble | width | minimum breaking load | weight per 100 pcs |
|----------|--------|-------------------------|-------|-----------------------|--------------------|
| a mm     | b mm   | c mm                    | d mm  | kg                    | kg                 |
| 4        | 40     | 4                       | 14    | -                     | 0.8                |
| 5        | 50     | 5                       | 16    | 100                   | 1.6                |
| 6        | 60     | 6                       | 18    | 120                   | 2.6                |
| 7        | 70     | 7                       | 22    | 180                   | 4.4                |
| 8        | 80     | 10                      | 24    | 300                   | 6.4                |
| 9        | 90     | 12                      | 26    | 330                   | 9.3                |
| 10       | 100    | 13                      | 30    | 460                   | 12.5               |
| 11       | 120    | 13                      | 36    | 600                   | 19.5               |
| 12       | 140    | 15                      | 40    | 680                   | 25.0               |
| 13       | 160    | 17                      | 44    | 800                   | 35.0               |