



Quick Links

standard type

- **Material** : mild steel
- **Finish** : electro-galvanised
- **Note** : the minimum breaking load shown below is for guidance only
the product is not suitable for lifting purposes

diameter	width inside	length inside	opening	minimum breaking load	weight per 100 pcs
a mm	b mm	c mm	d mm	kg	kg
3.5	10	29	5	240	0.9
4	11	32	5	300	1.3
5	13	39	6	540	2.0
6	14	46	7	750	3.3
7	16	51	8	1125	5.3
8	17	59	10	1500	7.5
9	17	64	11	2000	10.3
10	20	70	12	2400	13.0
12	23	83	14	3600	25.0



Quick Links

with enlarged opening

- **Material** : mild steel
- **Finish** : electro-galvanised
- **Note** : the minimum breaking load shown below is for guidance only
the product is not suitable for lifting purposes

diameter	width inside	length inside	opening	minimum breaking load	weight per 100 pcs
a mm	b mm	c mm	d mm	kg	kg
3.5	10	39	10	240	0.9
4	12	45	11	300	1.4
5	14	52	13	540	2.5
6	16	58	14	750	4.2
8	19	73	17	1500	9.4
10	22	88	20	2400	17.5
12	25	102	23	3600	28.2