

Chainslings Grade 10

1 Leg

 Grade 10 chainslings can be assembled to your own requirements. We can supply chainslings ranging from 2 tonne to 21.65 tonne. Assembly can be single leg, 2 leg, 3 leg & 4 leg. (please see chart below to determine your requirements).

• Grade 10 has a 25% higher W.L.L. Than conventional grade 8





Clevis Latch Hook



Fitting Options





Safety hook Clevis Type

Clevis type Grab Hook

- Assembled to your exact requiremnents
- Swivel Hooks also available

Higher Capacity Lightweight Chains

	O.m.			a angle from leg to vertical		a angle from leg to vertical		Sling Configuration
CLAIN CONTRACTION								
α Angle	90°	0-45°	45-60°	0-45°	45-60°	0-45°	45-60°	α Angle
7mm	2.00	2.80	2.00	4.20	3.00	4.20	3.00	1
8mm	2.60	3.65	2.60	5.50	3.90	5.50	3.90	Working
10mm	4.00	5.60	4.00	8.40	6.00	8.40	6.00	Load Limit
13mm	6.80	9.50	6.80	14.30	10.20	14.30	10.20	In Tonnes
16mm	10.30	14.40	10.30	21.65	15.50	21.65	15.50	1



Chain Diameter

35