



Scissor pallet truck with manual-hydraulic lift model HU HS 10 B

Capacity 1000 kg,
fork height max. 800 mm

A combination of hand pallet truck and elevating platform for the transport and raising of palletised loads to various departments.

Features

- Safety control handle with the functions:
Quick-lift - lifting - lowering.
- Lowering speed can be finely metered for sensitive lowering of the load.
- One-stage hydraulic for increased robustness.
- Quick-lift for loads up to 250 kg.
- Overload protection by pressure relief valve.
- Safety supports guarantee sure standing when the forks are raised.
- Low noise and smooth running with standard tyres:
steer rollers and load rollers – polyurethane.

Technical data model HU HS 10 B

Model	HU HS 10 B
Art.-No.	26600020
Capacity Q, kg	1000
Load center c, mm	600
Weight, kg	122
Tyre type ¹	PUR/PUR
Steering rollers, mm	180x50
Load rollers, mm	75x50
Number of wheels/load rollers	2/2
Stroke h ₃ , mm	715
Height of control handle max. h ₁₄ , mm	1254
Fork height lowered h ₁₃ , mm	85
Overall length L ₁ , mm	1725
Overall width b ₁ /b ₂ , mm	575
Fork height s, mm	45
Fork width e, mm	160
Fork length l, mm	1170
Outside dimension of forks b ₅ , mm	540
Ground clearance, wheelbase centre m ₂ , mm	18
Aisle width pallet A _{st} , mm	1986
Turning circle radius W _a , mm	1564

¹ PUR... Polyurethane

