

# CR 250 HORIZONTAL + VERTICAL

Self-locking device for vertical and horizontal operation



EN 360 VG11.060 VG11.062

ref no.: CR 250H V



67 cm - with a rope wound

SWIVEL

ENERGY ABSORBER

AZ 002ASI

AVAILABLE COLOURS



X-color



**NEW**



CR 250H + V self-locking device for vertical and horizontal operation in a plastic casing with a pull-down steel rope and a swivel mounted in the casing. The device has an additional shock-absorbing system located near the snap-hook. It is intended for work requiring considerable displacement in relation to the point of attachment. No need to use a safety shock absorber. No need to use AZ 800 cable when working horizontally.

**The CR 250H V self-locking device is a component of individual fall protection equipment.**



## SPECIAL FEATURES



TEST FOR MAXIMUM USER WEIGHT **120 kg**



VERTICAL USE OF THE DEVICE



DEVICE USE OF THE HORIZONTALLY



SECURITY FOR 1 PERSON

## PARAMETERS

Material:	composite housing, galvanized steel / stainless
Dimensions:	270 x 260 x 90 mm
Static strength:	min. 12 kN
Diameter of the cable:	5 mm (galvanized steel)

REF NO:	DEVICE LENGTH	WEIGHT
CR 250H V 06 X	6 m	4,80 kg
CR 250H V 08 X	8 m	5,00 kg
CR 250H V 11 X	11 m	5,50 kg
AX 323		

### Contact Us

Tel: 0808 123 69 69  
Fax: 0117 9381 602  
email: sales@safety-lifting.com

Unit R1D Rockingham Gate  
Cabot Park  
Poplar Way West  
BRISTOL  
BS11 0YW