


Method of lifting  
Number of legs  
Angle of inclination



Code	Load capacity [kg]									
PLE/N 6	1.120	1.120	2.240	2.240	1.500	1.120	2.300	1.600	1.120	1.120
PLE/N 8	2.000	2.000	4.000	4.000	2.800	2.000	4.200	3.000	2.000	2.000
PLE/N 10	3.150	3.150	6.300	6.300	4.400	3.150	6.600	4.700	3.150	3.150
PLE/N 13	5.300	5.300	10.600	10.600	7.400	5.300	11.200	7.900	5.300	5.300
PLE/N 16	8.000	8.000	16.000	16.000	11.300	8.000	16.900	12.000	8.000	8.000
PLE/N 22	15.000	15.000	30.000	30.000	21.000	15.000	31.800	22.500	15.000	15.000

Code	Load capacity [kg]	a [mm]	b [mm]	d [mm]	e [mm]	f [mm]	h [mm]	l [mm]	Weight [kg/pc.]
PLE/N 6	1.120	36	40	11	67	42	26	35	0,31
PLE/N 8	2.000	37	42	13	73	45	28	37	0,40
PLE/N 10	3.150	41	45	16,50	80	47	34	40	0,63
PLE/N 13	5.300	61	55	22	97	53	44	50	1,48
PLE/N 16	8.000	63	70	25	120	73	48	64	2,30
PLE/N 22	15.000	89	97	33	163	92	70	90	5,40

**Safety factor 4**  
Important: Subject to technical changes!