


Hydraulic Cylinders



- ◆ Chrome plated cylinder & ram
- ◆ Capacity: 5 - 100 tonne
- ◆ Spring return
- ◆ Stroke: 50-200mm
- ◆ Maximum pressure 700 bar
- ◆ Hydraulic coupler 3/8 npt
- ◆ Can be used in any position
- ◆ Lightweight aluminium cylinders also available
- ◆ 200 tonne-500 tonne made to order

A S - 5 5

- Stroke , 50mm
- Capacity, 5 tonne
- SINGLE-ACTING
- ACTIONRAM

Model	Cylinder Capacity (tonne)	Stroke (mm)	Cylinder Effective Area (cm ²)	Oil Capacity (cc)	Retracted Height	Extended Height	Cylinder Out Dia.	Cylinder Bore Dia.	Piston Rod Dia.	Base to Inlet Port	Weight (Kgs)
					A	B					
AS-55	5	50	6.38	35	134	184	38	28.5	25	25	1.1
AS-510		100		70	184	284					1.4
AS-515		150		106	234	384					1.8
AS-520		200		140	284	484					2.2
AS-105	10	50	15.2	76	133	183	62	44	38	20	2.1
AS-1010		100		152	183	283					3.4
AS-1015		150		228	233	383					4.8
AS-1020		200		304	283	483					5.6
AS-205	20	50	33.18	166	160	210	88	65	58	35	7
AS-2010		100		332	210	310					8.8
AS-2015		150		498	260	410					11
AS-2020		200		664	310	510					12.7
AS-305	30	50	44.18	220	165	215	102	75	68	35	9.8
AS-3010		100		440	215	315					12.5
AS-3015		150		660	265	415					16
AS-3020		200		880	315	515					17.5
AS-505	50	50	70.88	355	173	223	127	95	85	35	15.8
AS-5010		100		710	223	323					20
AS-5015		150		1070	273	423					23.5
AS-5020		200		1425	323	523					27.7
AS-1005	100	50	132.7	664	191	241	178	130	110	40	18
AS-1010		100		1330	226	326					38.8
AS-10015		150		1991	291	441					49.2