

PS45 - Premium Clip-On Ear Defenders

Collection: Hearing Protection

Range: Hearing Protection

Materials: ABS, PU, PVC, Polyoxymethylene, Stainless Steel

Product information

Premium Clip-On Ear Defenders using the same cup as our PS46 Premium Ear Defenders. Easy to clip-on and compatible with Endurance, Height Endurance and Expertbase safety helmets. Warning: attenuation performances vary depending on the helmet style they are used with.

Standards

EN 352-3:2002 (SNR 25dB)



Hearing Protection


Hearing problems occur when you are exposed to hazardous working conditions without wearing the correct protective equipment.

Hearing Protection

Hearing problems occur when you are exposed to hazardous working conditions without wearing the correct protective equipment.

Features

- Easy to clip-on
- Adjustable dual pin system provides multiple positioning for better fit
- Stand-off position for intermittent use
- Compatible with Endurance and Height Endurance helmets
- Compatible with Expertbase Helmets
- CE certified
- CE-CAT III
- UKCA marked
- Retail bag which aids presentation for retail sales
- Individually packed for vending machines



PS45 - Premium Clip-On Ear Defenders

Commodity Code: 6506101000

Test House

SATRA Technology Europe Ltd (Notified Body No.: NB: 2777)
 Bracetown Business Park
 D15 YN2P, Ireland
 Cert No: 2777/13982-01/E00-00

SATRA Technology Centre Ltd (Notified Body No.: AB: 0321)
 SATRA Technology Park
 NN16 8SD, United Kingdom
 Cert No: AB0321/18792-01/E00-00

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	DUN14
PS45GRR	Grey	65.0	43.0	60.0	0.3300	0.1677	5036108326082	15036108814869

PERFORMANCES - SOUND ATTENUATION - EN 352-3:2002

PS45										
A	Frequency (Hz)	63	125	250	500	1000	2000	4000	8000	
B	Mean Attenuation (dB)	10.5	11	20.6	27.9	38.0	33.4	34.1	30.3	
C	Standard Deviation (dB)	6.7	5.3	5.7	5.0	4.8	4.2	4.4	6.6	
D	Assumed Protection (dB)	3.8	5.7	14.9	22.8	33.2	29.1	29.7	23.7	
SNR 25dB H:29dB M: 24dB L: 14dB										

PS45GRR