## **INSUL8-P Fibreglass Professional Platform Step**



#### **Specifications**

Brand: TB DaviesWarranty: 3-yearMax Load: 150kg

Standard: EN131 PROFESSIONAL
Material: GRP Fibreglass/Aluminium
Commodity Code: 7019900085
Country of Origin: CN
Recommended Usage: Regular

#### **Common Dimensions**

- Tread Depth: 80mm

- Distance Between Treads: 280mm

- Storage Depth: 153mm

- Top Platform Tread (LxW): 345 x 255mm

- Handrail Height: 607mm

#### **Availability & Delivery**

Stock item. Delivery next day. (See exceptions, if applicable, overleaf)

[Representative image of product]

#### **Product Description**

Our Heavy-Duty Fibreglass step ladder range incorporates a multi-functional tool tray with non-conductive stiles, making them ideal for working around electricity. The combination of super-strong C-section fibreglass stiles and reinforced aluminium treads gives you a durable yet lightweight and easy to handle step that is perfect for the busy trades-person.

#### **Features**

- Non-conductive fibreglass stiles to 30,000 volts (EN61478), ideal for working around electricity
- Integrated multi-function tool tray
- Reinforced 320 x 248mm checker-plate platform (platform steps only)
- Comfortable 80mm treads
- Hinged metal locking stays, provide optimal stability
- Box section back legs with heavy-duty bracing
- Large feet angled to maximise ground contact and reduce slip

Please note that products marked 'Special Order' cannot be cancelled and are non-returnable once orders are acknowledged and placed.

This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.

# **INSUL8-P Fibreglass Professional Platform Step**

### **Product Dimensions**

SKU	Treads <sup>2</sup>	Approx. Working Height <sup>1</sup> (mm)	Platform Height (mm)	Closed Height (mm)	Width (mm)	Open Depth (mm)	Nett Weight (kg)
1236-004	4	2641	1041	1808	537	994	8.8
1236-005	5	2903	1303	2088	572	1174	10.2
1236-006	6	3164	1564	2368	606	1354	11.4
1236-008	8	3687	2087	2928	674	1715	14.0

<sup>&</sup>lt;sup>1</sup> Working height is calculated as 1,600mm plus platform height or last climbing tread, whichever is appropriate. Ladders set at an angle of 75° degrees.

### **Shipping Dimensions**

SKU	Shipping Length (mm)	Shipping Width (mm)	Shipping Depth (mm)	Shipping Volume (m³)	Gross Weight (kg)
1236-004	1808	430	153	0.119	8.97
1236-005	2088	445	153	0.142	10.42
1236-006	2368	460	153	0.167	11.56
1236-008	2928	497	153	0.223	14.20

Packaging Material — Polythene Wrap & Cardboard Header Card

<sup>&</sup>lt;sup>2</sup> Treads includes top platform step/top cap tool tray tread