

## TR 225 N Standard equipment

- ✓ Work positioning lever
- ✓ IP67 plug
- ✓ Trolley available for use with a gantry
- ✓ Upper limit safety device
- ✓ Self-braking motor with magnetic device
- ✓ Bracket can be extended up to 1120mm

## Applications

The low noise level allows working without causing noise harmful to the operator's health and bothersome to others.



### UPPER LIMIT SAFETY DEVICE

All hoists are fitted with upper limit safety device with positive drive by thrust spring that stops the upward movement of the load in the highest point.

### ARS DEVICE (ANTI REWINDING SYSTEM)

Models TR 225 N, TR 225 VN are fitted with the ARS device. This exclusive, lever/limit switch patented by Imer prevents reversing of the rope winding on the drum and keeps the machine damage-free.

<b>110V/50HZ</b>	<b>230V/50HZ</b>
<b>MOTOR AVAILABLE</b>	
<b>✓ TR 225 N</b>	

		TR 225N
Maximum capacity	kg	200
Av. full load lifting speed min/max	m/min	19
Max. working height	m	30
Ø wire rope	mm	5
Rope length	m	30
Motor power rate 230V/50Hz 110V/50Hz	kW	0.75
Motor speed	rpm	1360/1380
Running current	A	14/7.2
Machine weight	kg	44/46
SPL in operator's position	dB(A)	<70
Dimensions w/l closed (open) /h	mm	330/770(1170)/520
Packing dimensions w/l/h	mm	350/820/500