

LASER horizontal anchor line 10m

LH10

Tensioned horizontal 13mm rope to provide a temporary anchor point for two people.

Features:

- Up to 18m span
- Rated for 2 people
- Suitable for restraint or fall arrest
- Easy to adjust and release.
- Dissipates energy from a fall with no damage to rope or adjuster

Approved for up to 18m span with no intermediate anchor points required. Can be used by two people simultaneously, even in fall arrest.

Suitable for restraint or fall arrest. If access is required over a large area a Piranha adjustable lanyard can be attached to the Laser allowing independent adjustment of the users position in two perpendicular directions.

Adjusted and tensioned by hand. The adjuster will not damage the rope even after a two person fall arrest impact.

Options:

LH10 - 10m LH18 - 18m LH25 - 25m (span lengths above 18m use for restraint only)



Specifications:

Size: 10m

EN Test Mass: n/a

Loading: 2 persons. 250 kg (125 x 2)

Conformity: EN795(C)

Materials: Nylon and stainless steel

Weight (kg): 1.40

Industries: Rope access, roof safety, utilities, telecoms and fall arrest

All our PPE, rescue and lifting equipment have both UKCA and CE conformity where applicable

heightec - designing and manufacturing innovative products for specialist height safety and rescue since 1997

sales support: admin@heightec.com

heightec.com

NB: specifications and colour may change without notice.