

Working pressure 700 bar

All these pumps are one-way for single-acting applications. HHB-700C is supplied with 1.2-meter length high pressure hose. Other pumps are supplied with 1.8-meter length high pressure hose.

HHB-700B comes with pressure gauge and gauge adaptor .

Characteristics:

- •Robust, durable and compact.
- •Two-speed hydraulic system for fast and easy operation.
- •Lower handle effort to minimize operator fatigue.

•Large and comfortable release knob for improved control of pressure release.

- •Internal pressure relief valve for overload protection.
- •Supplied with R2 3/8 quick coupler and dust cap.





HHB-700C



HHB-700B

Т



Model	Working pressure (bar)		Oil displacement per stroke (cm³)		Reservior (cm³)		Dimensions (mm)			Packing size (cm)	Weight (Kg)
	Low pressure	High pressure	Low pressure	High pressure	Oil capacity	Usable oil	L	В	Н		
	stage	stage	stage	stage	capacity	capacity					
HHB-700	20	700	13	1.6	1000	700	600	120	200	73×19×19	10.6
HHB-700A	20	700	13	2.3	3200	2700	715	120	200	82×18×18	16.8
HHB-700B	20	700	13	2.3	1000	700	600	120	240	75×18×27	12.4
HHB-700C	20	700	8	1	600	350	380	120	140	60×16×17	5.6

SAFETYLIFTIN GEAR.COM

Contact Us

Tel: 0808 123 69 69 Fax: 0117 9381 602 Email: sales@safetyliftingear.com Unit R1D Rockingham Gate Poplar Way West Cabot Park Bristol BS11 0YW