

FW64 - Steelite Trekker Shoe S1P

Collection: Steelite™ Work

Upper: Cow Suede Leather

Sole: PU/PU

Outer Carton: 12

Steelite™ Work

Fully Compliant with all current standards, ideal for industrial wear with a strong and flexible construction.

Foot Protection

Innovation, design, styling and quality components define the Portwest foot protection collection.

Standards

EN ISO 20345: 2011 S1P



Features

- 3D breathable mesh lining
 - Available in unisex sizing
 - Back pull-tab for ease of getting onto the foot
 - Suede and textile upper
 - Padded collar for added comfort
 - Made with cow suede leather for a premium finish
 - CE certified
 - UKCA marked
 - Protective steel toecap
 - Pierce resistant steel midsole
 - Anti-static footwear
-

FW64 - Steelite Trekker Shoe S1P
Commodity Code: 6403400000

Test House
Intertek Italia S.p.A. (Notified Body No.: NB: 2575)
Via Guido Miglioli 2/A,
-, Italy
Cert No: LECFI00378437

ITS Testing Services (UK) Ltd. (Intertek) (Notified Body No.: 0362)
Centre Court
LE19 1WD, UK
Cert No: LECFI00382673

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m³)	EAN13	GTIN/DUN14
FW64BKR36	Black	63.0	47.0	37.0	1.3400	0.1096	5036108203499	25036108692167
FW64BKR37	Black	63.0	47.0	37.0	1.3800	0.1096	5036108164752	25036108630800
FW64BKR38	Black	63.0	47.0	37.0	1.4000	0.1096	5036108164769	25036108630817
FW64BKR39	Black	63.0	47.0	37.0	1.1900	0.1096	5036108164776	25036108630824
FW64BKR40	Black	63.0	47.0	37.0	1.1900	0.1096	5036108164783	25036108630831
FW64BKR41	Black	63.0	47.0	37.0	1.4000	0.1096	5036108164790	25036108630848
FW64BKR42	Black	66.0	49.0	37.0	1.3600	0.1197	5036108164806	25036108630855
FW64BKR43	Black	66.0	49.0	37.0	1.3900	0.1197	5036108164813	25036108630862
FW64BKR44	Black	66.0	49.0	37.0	1.4200	0.1197	5036108164820	25036108630879
FW64BKR45	Black	69.0	51.0	37.0	1.5300	0.1302	5036108164837	25036108630886
FW64BKR46	Black	69.0	51.0	37.0	1.5100	0.1302	5036108164844	25036108630893
FW64BKR47	Black	69.0	51.0	37.0	1.6000	0.1302	5036108164851	25036108630909
FW64BKR48	Black	69.0	51.0	37.0	1.5800	0.1302	5036108203505	25036108692174